



Bearing No. 68/710

Size	710x870x74 mm
Bore Diameter	710 mm
Outer Diameter	870 mm
Width	74 mm
d	710 mm
D	870 mm
B	74 mm
C	74 mm
r min.	4 mm
da min.	756 mm
Da max.	836 mm
ra max.	3 mm
Weight	92,6 Kg
Basic dynamic load rating (C)	480 kN
Basic static load rating (C0)	1100 kN
SRI	24.65
hidYobi	68/710
LangID	1
D_	870
SREX	0.08
B_	74
CAD	<a href="https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&amp;language=ja&amp;info=nsk_rb/roller_bearings/deep_groove_bb/single_row_dgbb/open_type_asmtab.pj&amp;varset={STAN=_},{ORDER=68/710},{SD=710},{D=870},{B=74},{R=4.0},{CR1=480000},{COR">https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&amp;language=ja&amp;info=nsk_rb/roller_bearings/deep_groove_bb/single_row_dgbb/open_type_asmtab.pj&amp;varset={STAN=_},{ORDER=68/710},{SD=710},{D=870},{B=74},{R=4.0},{CR1=480000},{COR</a>

	{1=1100000},{FO=17.4},{LG=480},{LO=560},{DAM1=726.0},{DA1=0.0},{DA2=854.0},{RA=3.0},{MASS=92.600}
da min	726
hidTable	ecat_NSRDGB
Oil rpm	560
SRE	24.65
mass	92.6
GRS rpm	480
ra	3
SRIX	0.08
D_a	854
SRIN	-0.08
C0	1100
fo	17.4
SREN	-0.08
DE_	837.625
Prod_Type3	DGBB_SR_OT
DA_	47.625
bomp	0
Z_	28
yobi	68/710
C_conv	480000
ALPHA_	0
SDM_	790
r	4
KBRG	6104
SBRG	18
DI_	742.375
calcUrl	/BearingGuide/html/calculation.jsp