



Bearing No. 6034

| | |
|-------------------------------|------------------|
| Size | 170x260x42 mm |
| Bore Diameter | 170 mm |
| Outer Diameter | 260 mm |
| Width | 42 mm |
| d | 170 mm |
| D | 260 mm |
| B | 42 mm |
| C | 42 mm |
| r min. | 2.1 mm |
| da min. | 179 mm |
| Da max. | 251 mm |
| ra max. | 2.0 mm |
| Weight | 7.92 Kg |
| Basic dynamic load rating (C) | 161 kN |
| Basic static load rating (C0) | 160 kN |
| (Grease) Lubrication Speed | 2200 r/min |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 170 mm |
| Outside Diameter | 260 mm |
| Width | 42 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| Dynamic Load Rating | 161,000 N |
| Static Load Rating | 160,000 N |
| Limiting Speed - Grease | 2,400 rpm |
| Limiting Speed - Oil | 2,800 rpm |
| Factor fo | 15.7 |

6034 NACHI Deep Groove Ball Bearings

| | |
|------------------|-------------------|
| Radial Clearance | 0.020 to 0.061 mm |
| da (min) | 179 mm |
| Da (max) | 251 mm |
| ra (max) | 2 mm |