



Bearing No. 635ZZ

Size	5x19x6 mm
Bore Diameter	5 mm
Outer Diameter	19 mm
Width	6 mm
d	5 mm
D	19 mm
B	6 mm
C	6 mm
r min.	0,3 mm
da min.	7 mm
da max	9,5 mm
Da max.	17 mm
ra max.	0,3 mm
Basic dynamic load rating (C)	2,34 kN
Basic static load rating (C0)	0,885 kN
(Grease) Lubrication Speed	34 000 r/min
Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359404661
Product Group - BDI	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing

Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	5MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove Shell Alvania Prelubricated
Category - BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Bore	0.197 Inch 5 Millimeter
Outside Diameter	0.748 Inch 19 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	5 mm
static load capacity:	885000 N
outside diameter:	19 mm
precision rating:	ISO Class 0
overall width:	6 mm
finish/coating:	Uncoated

635ZZ NTN Deep Groove Ball Bearings

bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	6 mm
snap ring included:	Without Snap Ring
outer ring width:	6 mm
internal clearance:	CN
maximum rpm (grease):	34000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	0.3 mm
dynamic load capacity:	2340 N
manufacturer product page:	Click here