



Bearing No. NU1048

Bore Diameter	240 mm
Outer Diameter	330 mm
d	240 mm
Fw	270 mm
D	360 mm
Ew	330 mm
B	56 mm
C	56 mm
r min.	3 mm
r1 min.	3 mm
da min.	253 mm
ra max.	2,5 mm
rb max.	2,5 mm
Weight	19,5 Kg
Basic dynamic load rating (C)	530 kN
Basic static load rating (C0)	820 kN
(Grease) Lubrication Speed	1 600 r/min
hidYobi	NU1048
LangID	1
D_	360
B_	56
CAD	https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&language=ja&info=nsk_rb/roller_bearings/cilindrical_rb/single_row_crb/nu_asmtab.prj&varset={STAN=Standard},{ORDER=NU1048},{CAGE=Standard},{SD=240},{D=360},{

	B=56},{R=3.0},{R1=3.0},{FW=270.0},{CR1=530000},{COR1=820000},{LT=2200},{LM=-},{LG=1600},{LO=2000},{DBB1=253.0},{DBB2=266},{DA2=347.0},{RA=2.5},{RB=2.5},{MASS=19.500}
hidTable	ecat_NSCLDR
Oil rpm	2000
rb	2.5
mass	19.5
GRS rpm	1600
ra	2.5
db max	266
TSR rpm	2200
C0	820
DE_	330
Prod_Type3	CRB_SR_NU
da	253
DA_	30
Z_	25
D_a max	347
yobi	NU1048
C_conv	530000
ALPHA_	0
SDM_	300
r	3
db min	253
dc min	275
KBRG	4144
SBRG	10
r1	3
DI_	270

calcUrl	/BearingGuide/html/calculation.jsp
---------	------------------------------------