



Bearing No. NJ1026

Size	130x200x33 mm
Bore Diameter	130 mm
Outer Diameter	200 mm
Width	33 mm
d	130 mm
Fw	148 mm
D	200 mm
B	33 mm
C	33 mm
r min.	2 mm
r1 min.	1,1 mm
da min.	139 mm
db max.	146 mm
db min	136,5 mm
ra max.	2 mm
rb max.	1 mm
Db max	191 mm
Weight	3,66 Kg
Basic dynamic load rating (C)	172 kN
Basic static load rating (C0)	238 kN
(Grease) Lubrication Speed	3 200 r/min
hidYobi	NJ1026
LangID	1
D_	200
B_	33
CAD	<a href="https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&amp;language=ja&amp;info=nsk_rb/">https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&amp;language=ja&amp;info=nsk_rb/</a>

	roller_bearings/cilindrical _rb/single_row_crb/nj_a smtab.prj&varset={STA N=Standard},{ORDER= NJ1026},{CAGE=Standa rd},{SD=130},{D=200},{B =33},{R=2.0},{R1=1.1},{ FW=148.0},{CR1=17200 0},{COR1=238000},{LT= 4000},{LM=-},{LG=3200 ,{LO=3800},{DA1=139.0 },{DBB1=136.50000},{D BB2=146},{DA2=191.0}, {RA=2.0},{RB=1.0},{MA SS=3.660}
hidTable	ecat_NSCLDR
Oil rpm	3800
rb	1
mass	3.76
GRS rpm	3200
ra	2
db max	146
TSR rpm	4000
C0	238
DE_	182
Prod_Type3	CRB_SR_NJ
da	139
DA_	17
Z_	23
D_a max	191
yobi	NJ1026
C_conv	172000
ALPHA_	0
SDM_	165
r	2
dc min	151

KBRG	4154
SBRG	10
r1	1.1
DI_	148
calcUrl	/BearingGuide/html/calculation.jsp