



Bearing No. 22326CKE4

Size	130x280x93 mm
Bore Diameter	130 mm
Outer Diameter	280 mm
Width	93 mm
d	130 mm
D	280 mm
B	93 mm
C	93 mm
r min.	4 mm
da min.	148 mm
da max	166 mm
Da min	236 mm
Da max.	262 mm
ra max.	3 mm
Weight	28,1 Kg
Basic dynamic load rating (C)	995 kN
Basic static load rating (C0)	1350 kN
(Grease) Lubrication Speed	1300 r/min
(Oil) Lubrication Speed	1600 r/min
Calculation factor (e)	0,34
Calculation factor (Y0)	1,9
Calculation factor (Y2)	2,9
Category	Bearings
BDI Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
EAN	0029176792557
Weight / US pound	28.1

Product Group - BDI	B04311
Y3	2
hidYobi	22326CKE4
LangID	1
Y1	1.9
D_	280
Y2	2.9
Macha rpm	0
B_	93
CAD	https://service.web2cad.co.jp/pcom/maker_login.php?Maker=NSK_RB&language=ja&info=nsk_rb/roller_bearings/spherical_rb/tapered_bore_asmta_b.prj&varset={STAN=-},{ORDER=22326CKE4},{SD=130},{D=280},{B=93.0},{R=4.0},{CR1=995000},{COR1=1350000},{LT=1800},{LM=-},{LG=1300},{LO=1600},{DA1=148},{DA2=166},{DA3=262},{DA4=236},{RA=3.0},{E=0.34},{Y2=2.9},{Y3=2.0},{Y0=1.9},{MASS=28.10}
da min	148
hidTable	ecat_NSSPHR
Oil rpm	1600
Y0	1.9
mass	28.1
GRS rpm	1300
ra	3
TSR rpm	1800
C0	1350
DE_	245.705
X0	1

Prod_Type3	SRB_CTB_TB
X1	1
X2	0.67
SIR	36
e	0.34
DA_	37.5
bomp	22326CKE4
Z_	15
ALP2	50
ALP1	12
ALP3	0
D_a max	262
D_a min	236
yobi	22326CKE4
ALPHA_	0.224
SDM_	209.142
r	4
KBRG	2322
SBRG	23
DI_	172.579
calcUrl	/BearingGuide/html/calculation.jsp