



Bearing No. MLE7005HVUJ74S

d1	32.2 mm
d2	30.25 mm
D1	42.65 mm
D2	44.25 mm
a	14 mm
Contact angle ?	25 °
rs min	0.6 mm
r1s min	0.3 mm
f0	7.83
Precision class	P4S
Mass	0.08 kg
Dynamic load, C	7.1 kN
Static load, C0	3.7 kN
Fatigue limit load, Cu	0.23 kN
Nlim (grease)	38,000 rpm
Axial displacement K Factor	0.84
Preload level	7
Preload value	0.06 kN
Axial rigidity	65 N/μm
Radial rigidity	144 N/μm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.32 Hz
Characteristic outer ring frequency, BPF0	7.3 Hz
Characteristic inner ring	9.7 Hz

frequency, BPI	
da min	29.5 mm
db min	29.5 mm
Da max	42.5 mm
Db max	42.5 mm
r1a max	0.3 mm
ra max	0.6 mm
D6	34.2 mm
Size	25x47x12 mm
Bore Diameter	25 mm
Outer Diameter	47 mm
Width	12 mm
d	25 mm
D	47 mm
B	12 mm
C	12 mm
Angle (?)	20 °