



Bearing No. 7209DB

| | |
|-------------------------------|------------------|
| Size | 45x85x19 mm |
| Bore Diameter | 45 mm |
| Outer Diameter | 85 mm |
| Width | 19 mm |
| d | 45 mm |
| D | 85 mm |
| B | 19 mm |
| C | 19 mm |
| Angle (?) | 30 ° |
| a | 9.3 mm |
| r min. | 1.1 mm |
| r1 min. | 0.6 mm |
| 2B | 38 mm |
| da min. | 50 mm |
| Da max. | 80 mm |
| ra max. | 0.6 mm |
| Weight | 0.430 Kg |
| Basic dynamic load rating (C) | 64,5 kN |
| Basic static load rating (C0) | 57,5 kN |
| (Grease) Lubrication Speed | 5500 r/min |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Duplex |
| Bore Size | 45 mm |
| Outside Diameter | 85 mm |
| Width | 19 mm |
| Fillet Radius/Chamfer | 1.1 mm |
| r1 | 0.6 mm |

| | |
|-------------------------|-----------|
| Dynamic Load Rating | 64,500 N |
| Static Load Rating | 57,500 N |
| Limiting Speed - Grease | 5,500 rpm |
| Limiting Speed - Oil | 7,500 rpm |
| da1 (min) | 52 mm |
| da2 (min) | 50 mm |
| Da1 (max) | 78 mm |
| Da2 (max) | 80 mm |
| ra (max) | 1 mm |
| ra1 (max) | 0.6 mm |