



Bearing No. 7008 ACD/P4A

Size	68x40x15 mm
Bore Diameter	68 mm
Outer Diameter	40 mm
Width	15 mm
d	40 mm
D	68 mm
B	15 mm
d ₁	49.2 mm
d ₂	49.2 mm
D ₁	58.8 mm
r _{1,2} - min.	1 mm
r _{3,4} - min.	0.3 mm
a	20.2 mm
d _a - min.	44.6 mm
d _b - min.	44.6 mm
D _a - max.	63.4 mm
D _b - max.	66 mm
r _a - max.	1 mm
r _b - max.	0.3 mm
d _n	50.8 mm
Basic dynamic load rating - C	15.9 kN
Basic static load rating - C ₀	10.4 kN
Fatigue load limit - P _u	0.44 kN
Limiting speed for grease lubrication	19000 r/min
Limiting speed for oil lubrication	30000 mm/min
Ball - D _w	7.938 mm

Ball - z	18
G _{ref}	2.4 cm ³
Calculation factor - e	0.68
Calculation factor - Y ₂	0.87
Calculation factor - Y ₀	0.38
Calculation factor - X ₂	0.41
Calculation factor - Y ₁	0.92
Calculation factor - Y ₂	1.41
Calculation factor - Y ₀	0.76
Calculation factor - X ₂	0.67
Preload class A - G _A	100 N
Preload class B - G _B	200 N
Preload class C - G _C	400 N
Preload class D - G _D	800 N
Calculation factor - f	1.06
Calculation factor - f ₁	0.99
Calculation factor - f _{2A}	1
Calculation factor - f _{2B}	1.02
Calculation factor - f _{2C}	1.05
Calculation factor - f _{2D}	1.08
Calculation factor - f _{HC}	1
Preload class A	96 N/micron
Preload class B	124 N/micron
Preload class C	162 N/micron
Preload class D	214 N/micron
Category	Precision Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	0.2
EAN	7316570704808
Product Group - BDI	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material - Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	25 Degree
Preload	None
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Flush Ground	No
Inch - Metric	Metric
Other Features	Single Row Angular Contact High Precision
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Raceway Type; Ball Bearing
Category - BDI	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7008 ACD/P4A
Weight / LBS	0.445

Outside Diameter	2.677 Inch 68 Millimeter
Width	0.591 Inch 15 Millimeter
Bore	1.575 Inch 40 Millimeter
bore diameter:	40 mm
radial static load capacity:	10.4 kN
outside diameter:	68 mm
maximum rpm (grease):	19000 rpm
overall width:	15 mm
maximum rpm (oil):	30000 rpm
contact angle:	25 °
bearing material:	Steel
duplex type:	Duplex Universal
cage material:	Cotton Fabric Reinforced Phenolic
closure type:	Open
fillet radius:	1 mm
precision rating:	P4
series:	70
operating temperature range:	300 °F
manufacturer product page:	Click here
radial dynamic load capacity:	15.9 kN
manufacturer upc number:	7316570704808
d ₁	49.2 mm
d ₂	49.2 mm
D ₁	58.8 mm
r _{1,2} min.	1 mm
r _{3,4} min.	0.3 mm

d_a min.	44.6 mm
d_b min.	44.6 mm
D_a max.	63.4 mm
D_b max.	66 mm
r_a max.	1 mm
r_b max.	0.3 mm
d_n	50.8 mm
Basic dynamic load rating C	15.9 kN
Basic static load rating C_0	10.4 kN
Fatigue load limit P_u	0.44 kN
Attainable speed for grease lubrication	19000 r/min
Attainable speed for oil-air lubrication	30000 r/min
Ball diameter D_w	7.938 mm
Number of balls z	18
Reference grease quantity G_{ref}	2.4 cm ³
Preload class A G_A	100 N
Static axial stiffness, preload class A	96 N/μm
Preload class B G_B	200 N
Static axial stiffness, preload class B	124 N/μm
Preload class C G_C	400 N
Static axial stiffness, preload class C	162 N/μm
Preload class D G_D	800 N
Static axial stiffness, preload class D	214 N/μm
Calculation factor f	1.06
Calculation factor f_1	0.99
Calculation factor f_{2A}	1

Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.19 kg