



Bearing No. QJ308

| | |
|-------------------------------|---|
| Size | 40x90x23 mm |
| Bore Diameter | 40 mm |
| Outer Diameter | 90 mm |
| Width | 23 mm |
| d | 40 mm |
| D | 90 mm |
| B | 23 mm |
| C | 23 mm |
| Angle (?) | 35 ° |
| a | 45,5 mm |
| r min. | 1,5 mm |
| da min. | 49 mm |
| da max | 81 mm |
| ra max. | 1,5 mm |
| Weight | 0,78 Kg |
| Basic dynamic load rating (C) | 67 kN |
| Basic static load rating (C0) | 100 kN |
| (Grease) Lubrication Speed | 6 300 r/min |
| SRI | 7.84 |
| hidYobi | QJ308 |
| LangID | 1 |
| ALP23 | 0 |
| ALP22 | 0 |
| D_ | 90 |
| ALP21 | 35 |
| SREX | 0.065 |
| B_ | 23 |
| CAD | http://service.web2cad.c |

| | |
|------------|---|
| | o.jp/pcom/?Maker=NSK _RB&info=nsk_rb/roller_ bearings/angular_contac t_bb/four_point_cbb_as mtab.prj&varset={STAN =-},{ORDER=QJ308},{S D=40},{D=90},{B=23},{R =1.5},{CR1=67000},{CO R1=100000},{CR2=6850 },{COR2=10200},{LG=6 300},{LO=8500},{AO=45 .5},{DA1=49},{DA2=81},{ RA=1.5},{MASS=0.78} |
| hidTable | ecat_NSANGFP |
| Oil rpm | 8500 |
| C0r | 10200 |
| SRE | 7.84 |
| mass | 0.78 |
| GRS rpm | 6300 |
| ra | 1.5 |
| SRIX | 0.065 |
| D_a | 81 |
| Cr | 6850 |
| SRIN | 0 |
| C0 | 100 |
| SREN | 0 |
| DE_ | 80.231 |
| Prod_Type3 | ACBB_FP_A |
| da | 49 |
| DA_ | 15.081 |
| Z_ | 11 |
| yobi | QJ308 |
| ao | 45.5 |
| SDM_ | 65 |
| r | 1.5 |
| KBRG | 7764 |

| | |
|---------|------------------------------------|
| DI_ | 49.759 |
| calcUrl | /BearingGuide/html/calculation.jsp |