



Bearing No. 2308SK

rs min	1.5 mm
Associated sleeve reference	H2308X
e	0.43
Y1	1.5
Y2	2.3
Y0	1.5
Radial clearance class	CN
Precision class	P0
Mass	0.89 kg
Dynamic load, C	45.5 kN
Static load, C0	13.5 kN
Nlim (oil)	8,000 rpm
Nlim (grease)	6,300 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	48 mm
da max	52 mm
db min	45 mm
Ce min	5 mm
Da max	82 mm
ra max	1.5 mm
Size	40x90x33 mm
Bore Diameter	40 mm
Outer Diameter	90 mm
Width	33 mm
d	40 mm
D	90 mm
B	33 mm

C	33 mm
r min.	1,5 mm
da min.	48 mm
Da max.	82 mm
ra max.	1,5 mm
Weight	0,889 Kg
Basic dynamic load rating (C)	45,5 kN
Basic static load rating (C0)	13,5 kN
(Grease) Lubrication Speed	6 300 r/min
(Oil) Lubrication Speed	8 000 r/min
Calculation factor (e)	0,43
Calculation factor (Y0)	1,5
Calculation factor (Y1)	1,5