



Bearing No. 2217SK

rs min	2 mm
Associated sleeve reference	H317X
e	0.25
Y1	2.5
Y2	3.9
Y0	2.6
Radial clearance class	CN
Precision class	P0
Mass	2.48 kg
Dynamic load, C	58.5 kN
Static load, C0	23.6 kN
Nlim (oil)	4,800 rpm
Nlim (grease)	3,800 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	94 mm
da max	104 mm
db min	91 mm
Ce min	12 mm
Da max	141 mm
ra max	2 mm
Size	85x150x36 mm
Bore Diameter	85 mm
Outer Diameter	150 mm
Width	36 mm
d	85 mm
D	150 mm
B	36 mm

C	36 mm
r min.	2 mm
da min.	94 mm
Da max.	141 mm
ra max.	2 mm
Weight	2,48 Kg
Basic dynamic load rating (C)	58,5 kN
Basic static load rating (C0)	23,6 kN
(Grease) Lubrication Speed	3 800 r/min
(Oil) Lubrication Speed	4 800 r/min
Calculation factor (e)	0,25
Calculation factor (Y0)	2,6
Calculation factor (Y1)	2,5